

# SUREFINISH



**SURECRETE**  
DESIGN PRODUCTS

Toll Free 1-800-544-8488  
Local 1-352-567-7973  
[www.SureCreteDesign.com](http://www.SureCreteDesign.com)

## Technical Data

### **COVERAGE**

*1<sup>st</sup> coat:*

approximately 1500 sq. ft  
per gal.

*Subsequent coats:*

2000-3000 sq. ft. per gal.

### **Packaging:**

1 Gallon Jug or

5 Gallon Pail

### **DESCRIPTION**

**SureFinish** beautifies and enhances resilient and non-resilient hard surface interior floors using any speed maintenance program. It is both easy to apply and maintain.

### **USE**

**SureFinish** is specifically designed to provide superior protection for interior **SureCrete** Stamp Overlays and Chemical Stains that have been sealed with any of **SureCrete's** sealers. **SureFinish** will enhance the luster.

### **APPLICATION**

After sealer has cured, SureFinish may be applied by mop. Protect the mop bucket with a trashcan liner to prevent contamination of **SureFinish**. The mop should be a closed loop mop head to prevent leaving "strings" in the finish product. Fully saturate the mop head and wring out so that mop is damp, but not dripping. Apply thin coats until desired initial gloss is achieved (usually 2-3 coats minimum). For optimum results burnish the first coat using a white or non-aggressive floor pad. Between coats allow the floor to dry to the touch and wait 15 additional minutes.

### **MAINTENANCE**

Dust mop daily using an untreated mop head to remove loose dirt, dust, and soil. Wet mop to clean ground in soil as needed. Machine scrub heavily soiled areas and reapply thin coats of **SureFinish** as needed. Heavily trafficked areas may require monthly reapplication.